

Technical Data Sheet

CODE 11123

MF 100/4"

Wall axial fans



Certifications



IMQ



CE



IMQ Performance



CCC




EAC

TECHNICAL AND PERFORMANCE DATA

Absorbed Current max (A)	0,09	Voltage (V)	220-240
Absorbed Power max (W)	15	Weight (Kg)	0,51
Frequency (Hz)	50	Delivery max (l/s)	24
Insulation Class	II°	Delivery max (m³/h)	85
IP	X4	Pressure max (mmH2O)	3
Max ambient temperature for continuous operation (°C)	50	Pressure max (Pa)	29
Nominal Diameter (mm)	100	RPM	2400
Ø Discharge Hole (mm)	98	Sound Pressure level Lp [dB (A)] 3m	31

DIMENSIONS



Etichetta Energetica	N0
Size A (mm)	159
Size B (mm)	17
Size C (mm)	77
Size D (mm)	98

Technical Data Sheet

CODE 11123

MF 100/4"


Wall axial fans



DESCRIPTION

- Material: UV resistant plastic (prevents ageing caused by exposure to sunlight).
- Nominal diameter 100 mm.
- Motor protected against thermal overload, with shaft turning in self-lubricating bushings, coupled to screw type thermoplastic impeller with wing profile blades.
- Maximum air flow: 85 m³/h.
- Non-return damper fitted to outlet port.
- IMQ SAFETY and IMQ PERFORMANCE certifications.
- Vortice speed controller.

CURVES



ACCESSORIES




C 1.5
(COMANDO EL.
1.5 A)

Code 12966



KIT SCB
(TRASF.E.C.)

Code 22481



SF 90-100

Code 22162